


TV4-203W




Specifications

System :	American TV standards
Channel coverage :	American VHF channels 2~13 American UHF channels 14~83 by using SONY UHF Converter
Picture tube :	4", 50-degree deflection, aluminized screen
Transistors :	31 (including Mesa and Epitaxial types)
Diodes :	17 (including Zener diode)
Silicon rectifier :	1 set
Resolution :	Vertical 350 lines, Horizontal 250 lines
Maximum sensitivity :	5 μ V/5 Vpp (in/out)
Automatic controls :	Pulse-operated AGC, Diode AFC Automatic Synchro-noise Suppressor
Speaker :	2" (5 cm), PM dynamic, 40 Ω
Audio output :	100 mW (undistorted)
Power requirements :	DC 12 V, 3.8 W AC 117 V, 50/60 cps, 6.2 W
Dimensions :	3-1/8" (H) \times 8-1/4" (W) \times 6-1/2" (D) (80 \times 210 \times 164 mm)
Weight :	5 lbs. 11ozs. (2.6 Kg) with battery
Glare proofing :	Smoked Filter, 70% Transparency


SONY®
SERVICING GUIDE

CONTENTS

	Page
Specifications for SONY Transistor TV4-203W	1
GENERAL	4
TUNER BLOCK	5
VIDEO SIGNAL BLOCK	6
DEFLECTION BLOCK	7
HIGH VOLTAGE BLOCK	7
POWER REGULATOR & SOUND SIGNAL BLOCK	7
PICTURE TUBE	8
METHOD OF DISASSEMBLING THE SET	9
To Remove the Cabinet Back	9
To Remove the Power Regulator & Sound Signal Circuit Board.....	9
To Remove the Video Signal Circuit Board	9
To Remove the Deflection Circuit Board	9
To Remove the Deflection Yoke	9
To Remove the Chassis Block	10
To Remove the Telescopic Antenna	10
To Remove the High Voltage Block	10
To Remove the Tuner	10
To Remove the Picture Tube	11
ADJUSTMENT AND ALIGNMENT	11
Video IF and Trap Alignment	11
Deflection Block Alignment	13
Horizontal Width Adjustment	14
Focus Adjustment	14
Power Regulator Board Alignment	14
TROUBLE SHOOTING	15~16
SCHEMATIC DIAGRAM	17~18
MOUNTING DIAGRAM	19~24
VOLTAGE DISTRIBUTION CHART	25~26
WAVE FORMS	26~27
PARTS LIST.....	28~33
EXPLODED DIAGRAM	34~38



(Fig. 1)



(Fig. 2)

General

The design was made to meet the following requirements.

- ### Electronic Informations of Each Section

Chassis Block

Battery Case

Power Regulator & Sound Signal Block

AC Cord with Power Rectifier

Cabinet Front

Speaker

Deflection Yoke

Control Knobs

Picture Tube

Cabinet Block

Video Signal Block


Deflection Block

Tuner Block

High Voltage Block


(Fig. 3)

Block Diagram



(Fig. 4)

Level Diagram for Video



Tuner Block

The Tuner uses three PNP Mesa Type Germanium Transistors (2SA161), one is used in the RF Amplifier, one is the Mixer and one in the Local Oscillator. A Disc Type Turret is used for mounting all the coils and contacts for Channel Selection. Special Contact Points have been designed for easy and positive channel selection. The transistors and other circuit parts are mounted directly above the Channel Switch and are enclosed within the Tuner Shield. RF coils for each channel are connected in series but the Oscillator Coil for each channel can be adjusted independently. The AGC characteristics of the set is excellent as the AGC action is extended to the IF Amplifier and to the RF Amplifier Stage in the VHF Tuner. The Set with the built-in Telescopic Antenna extended to its full length can be operated at a field strength of as much as 100 mV/m without overloading the circuit.


a. RF Amplifier

The Antenna Impedance is 75Ω . For correct impedance matching between the Antenna and the Transistor Input, taps are used on both sides of the tuned circuit. A tap on the Inductance is made on the Antenna side and a tap is made on the Capacitance on the Transistor side for impedance matching. The RF Transistor Output is double tuned with mutual coupling (double peaks). This in combination with the single peak of the input circuit gives essentially flat Bandwidth of 6 Mc for this stage.


A neutralizing capacitor is used in the base circuit as shown in Fig. 7-2 to prevent oscillation due to stray capacitance.

A gain of 14 dB is possible at 200 Mc with a circuit of this type but too much gain tends to make the Set unstable and hence the gain has been kept to be about 10 dB in our circuit. The gain on the lower channels tends to be higher than that on the higher channels, and so the damping resistors are inserted in the circuit of the lower channels to make the gain difference between the higher and lower channels within $\pm 1.5\text{ dB}$.


VHF Tuner




(Fig. 6-1)



(Fig. 6-2)



(Fig. 7-1)



(Fig. 7-2)

b. Mixer Circuit

The Mixer Transistor 2SA161 is emitter-grounded. The Impedance Matching is made by a capacitance divider in the same way as in the RF Amplifier. The Local Oscillator Signal is injected into the base of the transistor. The power dissipation in the mixer transistor is very much less (about $1/30$ — $1/50$) than the plate loss of the tube mixer. The voltage of the Local Oscillator Signal injected is about $0.2 V_{rms}$, which is also much smaller ($1/10$ — $1/20$) than that in tube mixer. Furthermore, the G_m of the Transistor Mixer is high and hence the trouble with the mixer noise encountered in tube circuits are of no consequence here in our circuit. This circuit is also neutralized to prevent undesired oscillation.

c. Local Oscillator

The Local Oscillator uses a Colpitts Circuit. This circuit is well suited for this use as it does not require a tap on the oscillator coil. The transistor (2SA161) is base-grounded. The drift is kept within 200 Kc. As mentioned before, each oscillator coil is independent of the others so that the oscillation frequency can be adjusted from outside the Tuner by turning the screw type cores. The Fine Tuning Capacitors are separately shielded to prevent radiation from the set. The adjustable range of the Local Oscillation is approx. 1.8 Mc for Channel 2 and approx. 5.5 Mc for Channel 13.

Video Signal Block


The Video Signal Block includes Video IF, AGC Section and Sound IF Amplifier. The Video IF is 26.75 Mc while the Sound IF is 22.25 Mc. The Band Width of this section is 3 Mc which is sufficient for this type of miniature Receiver. All Transistors used in VIF stage are PNP Mesa type Germanium Transistor (X1, 2, 3...2SA161~6). The Video Signal which is amplified and detected by this section is fed to Video Output Stage located on Deflection Block through Video Drive Transistor (X14, PNP Germanium). Sound Signals which are picked up at collector of X14 because of Intercarrier System are amplified by two Sound IF Stages and Detected Audio Signals are fed to Audio Amplifier which is placed on Power Regulator & Sound Signal Block.

Deflection Block

The Deflection Block consists of the Video Output, Synchronizing Pulse Separator and Vertical and Horizontal Deflection Circuits. A NPN Mesa Type Silicon Transistor (X15, 2SC115) is used in the Video Output Circuit in order to get 30 Vpp of output which is required for sufficient contrast of Picture Tube. The frequency response is almost flat to 3 Mc by the use of shunted series peaking (L501, R510). The Synchronizing Pulse is separated at X16 (NPN, 2SC73) and Vertical Pulse is taken out of X16 Collector. This stage is operated as a Noise Limiter for the Synchronizing Pulse to keep stable condition in a car or any other place. The Vertical Saw-tooth wave is generated by blocking oscillation in the circuit of X18 (NPN, 2SD65). It is then amplified by X19, X20, X21 (NPN, 2SD65) and X22 (PNP, 2SB381) and applied to the Vertical Deflection Yoke of the Picture Tube. Vertical output is used B class push-pull circuit which consists of X21 (NPN) and X22 (PNP) Transistors. As a result, receiver does not need Vertical Choke Coil and power consumption of this stage is very low. The Horizontal Deflection Pulse is generated by Horizontal Blocking Transformer (HBT) and X23 (PNP 2SB381) then amplified by X24 (PNP, 2SB382) which drives output stage. The Horizontal Output Transistor (X25, NPN Silicon Mesa Type 2SC41) is connected to the Horizontal Output Transformer and supplies the Saw-tooth wave to the Horizontal Deflection Yoke.

High Voltage Block

High Voltage Block consists of the Horizontal Output Transformer and five High Voltage Rectifiers (1SK2). All are covered by one metallic case. Fig. 8 shows the inside of High Voltage Block and Deflection Yoke. The Flyback Pulse is stepped up, and rectified by the High Voltage Rectifiers to the High Voltage of about 8 KV, then applied to the Anode of the Picture Tube.



(Fig. 8)


Power Regulator & Sound Signal Block

Power Regulator & Sound Signal Block includes Power Regulator and Audio Amplifier. Power Regulator & Sound Signal Circuit which has three transistors (X26, X27, PNP 2SB382 and X28, NPN 2SD64) keeps a constant voltage against the alternating Power Voltage and Current (See Circuit Board Alignment).


Detected Audio Signals through Volume Control (VR-1) are amplified by Audio Amplifier and supplied to Speaker. Direct Coupled Single Ended Push-Pull Circuit which requires neither Input nor Output Transformer is used at this audio power amplifier stage (X12, PNP 2SB382 and X13, NPN 2SD64). As a result, the size of audio amplifier is very small and audio power output is approx. 100 mW (non distorted) and maximum output is over 150 mW.

Picture Tube

The resolution of the picture greatly depends upon the construction of the Picture Tube, and the power consumption of the receiver is much influenced by the construction of the electron gun in the Tube. Therefore, the key point of success in making this type of Receiver is the improvement of picture tube. The CT-465 Picture Tube was specially developed for the SONY Transistor TV 4-203W and has the following features.



(Fig. 9)




(Fig. 10)

- Cathode Direct Heating System by High Frequency Power is used to get the picture immediately when the set is turned on and High Frequency Power is supplied by Horizontal Pulse Transformer in Deflection Block. (See Fig. 10)
- Deflection Power
50 degree deflection and 12.75 mm neck diameter result in lower deflection power although the anode voltage is as high as 8 KV. This gives a brightness of 500 lux

Specifications of Picture Tube CT-465

Type :	Rectangular Frame	Focusing :	Electrostatic Automatic
Neck Diameter :	12.75±0.35 mm	Full Length :	156 mm
Deflection :	Electromagnetic	Anode Voltage :	8 KV
Deflection Angle :	50 degree	1st Grid cut-off Voltage :	-20~-30V
Heater Voltage :	0.58 V, 300 mA		

Signal and Power Source Layout




Method of Disassembling the Set

To Remove Cabinet Back (See Fig. 12)

1. Untie two screws for battery case and remove battery case.
2. Remove two rubber foot screws and self tapping screw ($\oplus P 2.6 \times 6$) located on the rear of cabinet.
3. Remove one philips head screws on the top of the cabinet.
4. Remove two self tapping screws located on both side of the cabinet.
5. Grasp cabinet front and cabinet back and remove cabinet back by pulling.

Note: Carrying handle must be held when cabinet is removed.



(Fig. 12)

To Remove Power Regulator & Sound Signal Circuit Board (See Fig. 13)


1. Remove one philips head screw ($\oplus P 3 \times 5$) at tuner side.
2. Remove two plastic clear screws ($\oplus P 3 \times 5$) located on the back of the chassis.
3. Pull PC Board to make free from receiver.
4. Disconnect 7P Plug by pulling and lift PC Board off receiver.

To Remove Video Signal Circuit Board (See Fig. 14)

1. Place receiver upside down.
2. Remove two philips head screws 2 and 3 in the Fig. 14.
3. Lift the Video Signal Circuit Board and pull straight up.
4. Disconnect yellow wire and black co-axial cable (VIF in) by pulling.
5. Disconnect 7-P plug.

To Remove Deflection Circuit Board (See Fig. 14)


1. Remove one screw (① in Fig. 14) located on cabinet front.
2. Lift the Deflection Circuit Board and pull it off from Multi-jack.
3. Disconnect yellow and brown wires from Picture Tube Socket, red, blue, orange and white leads from High Voltage Block, and green and gray from Deflection Yoke. Above wires are removed by pulling at the terminal tip on Deflection Circuit Board.




(Fig. 13)

To Remove Deflection Yoke (See Fig. 15)

1. Remove cabinet back and video signal circuit board.
2. Disconnect picture tube socket.
3. Loosen the yoke clamp screw.
4. Remove deflection yoke carefully as the picture tube neck is very weak.



(Fig. 14)



(Fig. 15)

To Remove Chassis Block (See Fig. 16)

1. Remove all the control knobs located on front panel by pulling.
2. Remove cabinet, video signal and deflection circuit boards.
3. Remove CRT anode plug from picture tube.
4. Remove deflection yoke.
5. Remove four screws (+K 2.6×4) located at the top bottom and left side of the cabinet.
6. Loosen lead wires between cabinet front and picture tube by pulling.
7. Remove external antenna jack from cabinet front by unscrewing jack nut.
8. Unsolder white earphone jack lead at jack terminal.

Caution: When removing the channel selector knob, pull the fine tuning knob together to avoid any damage against the channel selector knob.

To Remove Telescopic Antenna


1. Remove chassis and cabinet front. (See chassis and front cabinet disassembly)
2. Remove one philips head screw (+P 3×5) and spring washer.
3. Unsolder co-axial cable and resistor. (carbon fixed 27KΩ)

To Remove High Voltage Block (See Fig. 17)


1. Remove cabinet back.
2. Remove power regulator sound signal circuit board and deflection circuit board. (See power regulator and deflection circuit boards disassembly)
3. Unsolder red and blue leads at the terminal on deflection circuit board.
4. Disconnect orange and white leads by pulling them up.
5. Remove anode plug from picture tube.
6. Remove two screws (+P 3×5) located on the rear of high voltage block.

To Remove Tuner (See Fig. 17)

1. Remove chassis and cabinet front. (See chassis and front cabinet disassembly)
2. Disconnect shielded wire at the external antenna jack by unsoldering.
3. Remove two philips head screws 4 and 5 in Fig. 14 and lift the tuner block up temporarily, then remove it by pulling to the right of the receiver.




(Fig. 16)




(Fig. 17)

1. Remove cabinet front from receiver
2. Place cabinet front with picture tube on its safety cover (face down) and protect the safety cover with a cloth.
3. Remove long screw (\oplus 3 \times 25) and nut at the picture tube clamp.
4. Remove picture tube clamp and clamp rod, and lift the tube up carefully.

The connection of Multi-jack terminal is as follows.



(Fig. 18)




(Fig. 19)

Video IF and Trap Alignment

Sweep Generator
Marker Generator
Oscilloscope
DC Power Supply
VTVM if available

1. Connect Sweep Generator to Tuner TP through 3pF Capacitor.
2. Set Sweep to approx. 25 Mc.
3. Couple Marker Generator to Video IF input.
4. Apply DC Voltmeter across 1000 Ω in CR301 and get 0.5 V in DC Voltmeter by adjusting the Attenuator of Sweep Generator.
5. Connect the Oscilloscope to the Video Detector Output.



(Fig. 20)

2. Trap Alignment


1. Set Marker Generator to 22.25 Mc.
2. Tune Trap-1 (22.25 Mc) and get minimum dip
3. Set Marker Generator to 28.25 Mc.
4. Tune Trap-2 (28.25 Mc) and get minimum dip.

3. Video IF Alignment

1. Set Marker Generator to 23.45 Mc for VIFT2 adjustment, then 26.75 Mc for VIFT3 adjustment
2. Get Standard Response Curve as shown in Fig. 21 by adjusting VIFT2 and VIFT3.

VIF Alignment chart is as follows.

Adjusting Point	Center Frequency	Band Width	Damping Resistors
VIFT 1 (built in Tuner)	24.3 Mc	3 Mc	
2	23.6 Mc	1 Mc	R305
3	26.3 Mc	1 Mc	R313
4	25.5 Mc	3 Mc	
5	26.75 Mc	3.8 Mc	



(Fig. 21)

Distribution of VIFT, SIFT & Detector Block


Standard Response Curve

4. Sound IF Alignment

Test Equipments

Sweep Generator
Marker Generator
Oscilloscope
Power Supply
VTVM


Connections (Refer to Fig. 23)



Standard Response for Sound Detector

(Fig. 22)

- Step 1. Set SSG to 4.5 Mc (AM 1,000c/s, 30% Modulation) and get the minimum voltage of meter by adjusting Trap-3.
- Step 2. Adjust SIFT1, 2 and 3 so as to get the S shaped wave shown in Fig. 22.



(Fig. 23)

Deflection Block Alignment

Following check and alignment are necessary when Deflection Circuit Board is replaced.

(1) CRT Heater Voltage Alignment

Test Equipment

Thermoelectric Voltmeter

Voltage across the heater terminal of picture tube must be less than 0.60 V (Connection, see Fig. 24).


If above voltage is more than 0.60 V, adjust resistor R511 so as to get less than 0.60 V.

(2) Vertical Height, Vertical Linearity, and Vertical Bias Controls.

Test Equipment

Volmeter (20 K Ω /V)

1. Set Deflection Circuit Board to Receiver and get normal Test pattern by adjusting VR-8 (Vertical Linearity) and VR-7 (Vertical Width).



(Fig. 24)

Caution

Voltage between the collectors of X20 & X21, and +10 V line should be $3.8\text{ V} \pm 0.2\text{ V}$. Voltage across emitter resistor (R711) of X22 (2SB381) should be $0.17\text{ V} \sim 0.18\text{ V}$. If not, adjust Vertical Bias Control (VR-9, 10).

Make sure no Retrace Line or white Vertical Bars on Raster present.


Horizontal width Adjustment

Set the Brightness to maximum by adjusting brightness control knob located on front panel and make sure horizontal width is normal. If not, add small value of capacitor (approx. $0.01 \sim 0.001 \mu\text{F}$) to C804 and get normal width.

Caution Recheck CRT heater voltage after the above adjustment.

Focus Adjustment

Connect DC Voltmeter as indicated below (Fig. 25) and get $2.4 \text{ V} \sim 2.6 \text{ V}$ in meter by adjusting Brightness Control Knob. Then adjust Semi-fixed Resistor (VR-12) so as to get the sharpest and the clearest picture.



(Fig. 25)

Power Regulator Board Alignment


Test Equipments	DC Power Supply
	DC Voltmeter
	DC Ammeter

Connection (refer to Fig. 26)

Apply 12 V DC in input and adjust VR-13 ($5 \text{ K}\Omega$) so as to get $10 \text{ V} \pm 0.2 \text{ V}$ in output.

Adjusted Power Regulator Board should satisfy the following features


- (1) When the input voltage is set 12 (Twelve Volts DC) and output current is changed from zero to 100 mA by adjusting output load, output voltage of this board should be held between 10 V and 10.6 V
- (2) Set the Input at 12 V and the Output Current at 370 mA, then change the Input from 10 V to 14 V DC under the condition of constant load. The Output Voltage should be maintained between 9.7 V to 10.3 V.




(Fig. 26)

— 15 —

— 16 —



Schematic Diagram




Δ To be adjusted

Mounting Diagram

—Printed Side—


—Video Signal Circuit Board—



Mounting Diagram

—Parts Side—


—Video Signal Circuit Board—





—Parts Side—


—Deflection Circuit Board—



Mounting Diagram

— Printed Side —


Power Regulator & Sound Signal Circuit Board



Mounting Diagram


— Parts Side —

Power Regulator & Sound Signal Circuit Board



Wave Forms

—Deflection Circuit Board—



Electrical Parts List (A)

Part No.	Symbol	Description	Part No.	Symbol	Description
		Transistor	1-902-489-11	L ₂₀₉	Jumper Wire (B)
X ₂₀₁		2SA161 (RF)	1-425-052-11	L ₂₁₀	RF Coil
X ₂₀₂		2SA161 (MIX)	-051-12	L ₂₁₁	"
X ₂₀₃		2SA161 (OSC)	-051-12	L ₂₁₂	"
X ₁		2SA166 (1st VIF AMP)	1-407-035-12	L ₂₁₃	Micro Inductor
X ₂		2SA163 (2nd VIF AMP)	-052-11	L ₂₁₄	"
X ₃		2SA162 (3rd VIF AMP)	1-902-601-11	L ₂₁₅	Jumper Wire (C)
X ₄		2SA70 (1st AGC AMP)	1-407-052-11	L ₃₀₁	Micro Inductor
X ₅		2SC73 (2nd AGC AMP)	1-409-034-11	TRAP ₁	Trap Coil (22.25 Mc)
X ₆		2SB379 (3rd AGC AMP)	-035-11	TRAP ₂	" (28.25 Mc)
X ₇		2SB381 (4th AGC AMP)	-033-11	TRAP ₃	" (4.5 Mc)
X ₈		2SA122 (2nd SIF AMP)	1-403-434-11	VIFT ₂	Video IF Transformer (23.6 Mc)
X ₉		2SA122 (3rd SIF AMP)	-435-11	VIFT ₃	" (26.3 Mc)
X ₁₀		2SD64 (AF DRIVE)	-437-11	VIFT ₄	" (25.5 Mc)
X ₁₁		2SB379 (AF DRIVE)	-419-02	VIFT ₅	" (26.78 Mc)
X ₁₂		2SB382 (AF POW)	-314-11	SIFT ₁	Sound IF Transformer
X ₁₃		2SD64 (AF POW)	-315-11	SIFT ₂	"
X ₁₄		2SA323 (VD & 1st SIF AMP)	-313-11	SIFT ₃	"
X ₁₅		2SC115 (VD OUT)	-420-02	DET ₁	Detector Block
X ₁₆		2SC73 (SYNC SEP & NOISE LIMIT)	-431-11	DET ₂	"
X ₁₇		2SB382 (SYNC SPLIT)	1-231-001-11		AGC Block
X ₁₈		2SD65 (VERT OSC)	1-407-050-11	L ₅₀₁	Micro Inductor
X ₁₉		2SD65 (VERT DRIVE)	1-413-005-11	L ₈₀₁	Stabilizing Coil for Horizontal Sweep
X ₂₀		2SD65 (VERT OUT)			
X ₂₁		2SD65 (VERT OUT)	1-421-013-11	L ₈₀₂	Horizontal Choke Coil (25 μ H)
X ₂₂		2SB381 (VERT OUT)	1-435-008-11	VBT	Vertical Blocking Transformer
X ₂₃		2SB381 (HOR OSC)	-009-11	HBT	Horizontal Blocking Transformer
X ₂₄		2SB382 (HOR DRIVE)	1-437-003-11	HDT	Horizontal Driver Transformer
X ₂₅		2SC41 (HOR OUT)	1-425-098-11	HPT	Horizontal Pulse Transformer
X ₂₆		2SB382 (REG POW)	1-439-010-11	HOT	Horizontal Output Transformer
X ₂₇		2SB382 (REG POW)	1-441-121-11	PT	Power Transformer
X ₂₈		2SD64 (REG DRIVE)			
		Diode	1-221-412-11	VR ₁	Potentiometer
D ₁		1T261	-416-11	VR ₂	Volume Control 5 K Ω -T
D ₂		1T261	-415-11	VR ₃	Contrast Control 3 K Ω -C
D ₃		1T261	-414-11	VR ₄	Brightness Control 500 K Ω -B
D ₄		1T22	-413-11	VR ₅	Horizontal Hold Control 10 K Ω -B
D ₅		1T22	-410-11	VR ₆	Vertical Hold Control 2 K Ω -B
D ₆		1T23	-355-11	VR ₇	Semi-fixed Resistor 100 K Ω -B
D ₇		1T23	-355-11	VR ₈	Vertical Height Control 3 K Ω -B
D ₈		1T261	-327-00	VR ₉	Vertical Linearity Control 3 K Ω -B
D ₉		1T22	-408-11	VR ₁₀	Vertical Bias Control 10 K Ω -B
D ₁₀		1T22	-355-11	VR ₁₁	Vertical Bias Control 20 K Ω -B
D ₁₁		1T22			Horizontal Frequency Control
D ₁₂		1T22	-407-11	VR ₁₂	3 K Ω -B
D ₁₃		SD-1LA	-409-11	VR ₁₃	Focus Control 1 M Ω -B
D ₁₄		S2C40			Semi-fixed Resistor 5 K Ω -B
D ₁₅		SD-1LA			
D ₁₆		1S332	1-231-002-11	CR ₃₀₁	Encapsulated Component
D ₁₇		1T22	1-101-537-11	CR ₃₀₂	0.01 μ F \times 2, 1 K Ω
1-530-012-11	REC ₁	Silicon Rectifier S2TB	-537-11	CR ₃₀₃	0.01 μ F \times 2, 1.2 K Ω
-012-11	REC ₂	" S2TB	-537-11	CR ₄₀₁	0.01 μ F \times 2, 1.2 K Ω
			-536-11	CR ₄₀₂	500 PF \times 2, 3.3 K Ω \times 2
		Thermistor			Resistor
8-690-006-00	Th ₇₀₁	S-1250	1-203-027-11	R ₁₀₁	560 Ω RD $\frac{1}{4}$ L Carbon
1-800-007-12	Δ PTH ₇₀₁	10 K Ω (Positive)	1-204-103-11	R ₂₀₁	2.7 K Ω RD $\frac{1}{32}$ SL "
		Coil & Transformers	1-203-192-11	R ₂₀₂	15 K Ω RD $\frac{1}{16}$ L "
1-409-027-11	L ₂₀₁	IF Trap Coil (A)	1-204-101-11	R ₂₀₃	240 Ω RD $\frac{1}{32}$ SL "
1-425-083-11	L ₂₀₂	RF Coil (D)	-102-11	R ₂₀₄	1 K Ω " " "
-049-11	L ₂₀₃	RF Coil (A)	-104-11	R ₂₀₅	4.7 K Ω " " "
-050-11	L ₂₀₄	RF Coil (B)	1-203-192-11	R ₂₀₆	15 K Ω RD $\frac{1}{16}$ L "
1-409-028-11	L ₂₀₅	IF Trap Coil (B)	1-204-102-11	R ₂₀₇	1 K Ω RD $\frac{1}{32}$ SL "
1-403-432-11	L ₂₀₆	IF Transformer	-102-11	R ₂₀₈	1 K Ω " " "
1-425-104-12	L ₂₀₇	Compensation Coil for Fine Tuning	-102-11	R ₂₀₉	1 K Ω " " "
1-902-488-11	L ₂₀₈	Jumper Wire (A)	-103-11	R ₂₁₀	2.7 K Ω " " "

Δ Posistor is the thermistor which has positive characteristic of resistance against temperature.

—continued—

Part No.	Symbol	Description	Part No.	Symbol	Description
1-203-190-11	R ₂₁₁	10 K Ω RD $\frac{1}{16}$ L Carbon	1-203-326-00	R ₆₀₁	680 K Ω RD $\frac{1}{8}$ RL Carbon
1-204-103-11	R ₂₁₂	2.7 K Ω RD $\frac{1}{32}$ SL //	-326-00	R ₆₀₂	680 K Ω // //
-041-11	R ₂₁₃	240 Ω RD $\frac{1}{16}$ L //	-387-00	R ₆₀₃	22 K Ω // //
-080-11	R ₂₁₄	820 Ω // //	-759-00	R ₆₀₄	120 K Ω // //
-104-11	R ₂₁₅	4.7 K Ω RD $\frac{1}{32}$ SL //	-377-00	R ₆₀₅	5.1 K Ω // //
-109-11	R ₂₁₆	1.5 K Ω // //	-383-00	R ₆₀₆	10 K Ω // //
-103-11	R ₂₁₇	2.7 K Ω // //	-368-00	R ₆₀₇	1.2 K Ω // //
-103-11	R ₂₁₈	2.7 K Ω // //	-368-00	R ₆₀₈	1.2 K Ω // //
-105-11	R ₂₁₉	5.1 K Ω // //	-368-00	R ₆₀₉	1.2 K Ω // //
-104-11	R ₂₂₀	4.7 K Ω // //	-368-00	R ₆₁₀	1.2 K Ω // //
-105-11	R ₂₂₁	5.1 K Ω // //	-760-00	R ₆₁₁	430 Ω // //
1-203-594-00	R ₃₀₁	100 Ω RD $\frac{1}{16}$ L //	-381-00	R ₆₁₂	6.8 K Ω // //
	R ₃₀₂	—deleted—	-372-00	R ₆₁₃	2.7 K Ω // //
	R ₃₀₃	—deleted—	-393-00	R ₆₁₄	51 K Ω // //
1-203-421-00	R ₃₀₄	1 K Ω RD $\frac{1}{16}$ RL Carbon	-368-00	R ₆₁₅	1.2 K Ω // //
-186-00	*R ₃₀₅	5.6 K Ω // //	-376-00	R ₆₁₆	4.7 K Ω // //
-420-00	R ₃₀₆	470 Ω // //	-372-00	R ₆₁₇	2.7 K Ω // //
-428-00	R ₃₀₇	27 K Ω // //	-131-00	R ₇₀₁	7.5 K Ω RD $\frac{1}{4}$ L //
-420-00	R ₃₀₈	470 Ω // //	-151-00	R ₇₀₂	1.8 K Ω // //
-884-00	R ₃₀₉	33 K Ω // //	-061-00	R ₇₀₃	3.9 K Ω // //
-895-00	R ₃₁₀	27 Ω // //	-367-00	R ₇₀₄	1 K Ω // //
-447-00	R ₃₁₁	2.7 K Ω // //	-383-00	R ₇₀₅	10 K Ω // //
-629-00	R ₃₁₂	15 K Ω // //	-367-00	R ₇₀₆	1 K Ω // //
-190-00	*R ₃₁₃	10 K Ω RD $\frac{1}{16}$ L //	1-207-019-00	R ₇₀₇	3 Ω RW $\frac{1}{4}$ RL Wire Wound
-434-00	R ₃₁₄	3.3 K Ω RD $\frac{1}{16}$ RL //	1-203-370-00	R ₇₀₈	2.2 K Ω RD $\frac{1}{8}$ RL Carbon
-438-00	R ₃₁₅	6.8 K Ω // //	-378-00	R ₇₀₉	5.6 K Ω // //
-878-00	R ₃₁₆	3.9 K Ω // //	-391-00	R ₇₁₀	43 K Ω // //
-414-00	R ₃₁₇	47 Ω RD $\frac{1}{8}$ RL //	1-207-024-00	R ₇₁₁	8.2 Ω RW $\frac{1}{4}$ RL Wire Wound
-421-00	R ₃₁₈	1 K Ω // //	-042-00	R ₇₁₂	13 Ω // //
-427-00	R ₃₁₉	10 K Ω RD $\frac{1}{16}$ RL //	-042-00	R ₇₁₃	13 Ω // //
-420-00	R ₃₂₀	470 Ω // //	1-203-366-00	R ₇₁₄	820 Ω RD $\frac{1}{8}$ RL Carbon
-445-00	R ₃₂₁	560 Ω // //	-363-00	R ₇₁₅	560 Ω // //
-447-00	R ₃₂₂	2.7 K Ω // //	-363-00	R ₇₁₆	560 Ω // //
-447-00	R ₃₂₃	2.7 K Ω // //	-368-00	R ₇₁₇	1.2 K Ω // //
-621-00	R ₃₂₄	750 Ω // //	-759-00	R ₇₁₈	120 Ω // //
-422-00	R ₃₂₅	1.5 K Ω // //	-383-00	R ₇₁₉	10 K Ω // //
-421-00	R ₃₂₆	1 K Ω // //	-335-00	R ₈₀₁	750 Ω // //
-478-11	R ₃₂₇	47 Ω RD $\frac{1}{16}$ L //	-361-00	R ₈₀₂	470 Ω // //
-438-00	R ₄₀₁	6.8 K Ω RD $\frac{1}{16}$ RL //	-368-00	R ₈₀₃	1.2 K Ω // //
-892-00	R ₄₀₂	3.6 K Ω // //	-360-00	R ₈₀₄	330 Ω // //
-836-00	R ₄₀₃	2.4 K Ω // //	1-207-021-50	*R ₈₀₅	4.7 Ω RW $\frac{1}{4}$ RL Wire Wound
-447-00	R ₄₀₄	2.7 K Ω // //	1-203-384-00	R ₈₀₆	12 K Ω RD $\frac{1}{8}$ RL Carbon
-423-00	R ₄₀₅	2.2 K Ω // //	-399-00	R ₈₀₇	100 K Ω // //
-438-00	R ₄₀₆	6.8 K Ω // //	-363-00	R ₈₀₈	560 Ω // //
-446-00	R ₄₀₇	2 K Ω // //	-367-00	R ₈₀₉	1 K Ω // //
-420-00	R ₄₀₈	470 Ω // //	1-201-600-00	R ₈₁₀	1 M Ω RC $\frac{1}{2}$ L Composition
-427-00	R ₄₀₉	10 K Ω // //	-455-00	R ₈₁₁	1.5 M Ω // //
-422-00	R ₄₁₀	1.5 K Ω // //	1-207-058-11	R ₉₀₁	0.5 Ω RW $\frac{1}{4}$ RL Wire Wound
-780-00	R ₄₁₁	1.2 K Ω // //	-058-11	R ₉₀₂	0.5 Ω // //
-414-00	R ₄₁₂	47 Ω RD $\frac{1}{8}$ RL //	1-203-412-00	R ₉₀₃	390 Ω RD $\frac{1}{8}$ RL Carbon
-617-00	R ₅₀₁	150 K Ω RD $\frac{1}{16}$ RL //	-368-00	R ₉₀₄	1.2 K Ω // //
-428-00	R ₅₀₂	27 K Ω // //	-069-00	R ₉₀₅	10 K Ω RD $\frac{1}{4}$ L //
-892-00	R ₅₀₃	3.6 K Ω // //	-143-00	R ₉₀₆	390 Ω // //
-857-00	R ₅₀₄	620 Ω RD $\frac{1}{8}$ RL //	-061-00	R ₉₀₇	3.9 K Ω // //
-367-00	R ₅₀₅	1 K Ω // //	-367-00	R ₉₀₈	1 K Ω RD $\frac{1}{8}$ RL //
-373-00	*R ₅₀₆	3.3 K Ω // //	1-201-455-00	R ₉₀₉	1.5 M Ω RC $\frac{1}{2}$ L Composition
-611-00	R ₅₀₇	75 Ω // //	-455-00	R ₉₁₀	1.5 M Ω // //
-373-00	R ₅₀₈	3.3 K Ω // //			Capacitor
-383-00	R ₅₀₉	10 K Ω // //	1-101-562-11	C ₂₀₁	50 PF Ceramic
-395-00	R ₅₁₀	62 K Ω // //	1-141-060-11	C ₂₀₂	Cylindrical Trimmer Capacitor
1-207-058-00	*R ₅₁₁	0.5 Ω RW $\frac{1}{4}$ RL Wire Wound	1-101-575-11	C ₂₀₃	14 PF Ceramic
1-203-442-00	R ₅₁₂	470 K Ω RD $\frac{1}{8}$ RL Carbon	-561-11	C ₂₀₄	30 PF //
1-201-596-00	R ₅₁₃	3.3 M Ω RC $\frac{1}{2}$ L Composition	-565-11	C ₂₀₅	25 PF //
1-203-383-00	R ₆₀₁	10 K Ω RD $\frac{1}{8}$ RL Carbon	-568-11	C ₂₀₆	2.1 PF //
			-569-11	C ₂₀₇	12 PF //

* To be adjusted

—continued—

Part No.	Symbol	Description	Part No.	Symbol	Description
1-141-060-11	C ₂₀₈	Cylindrical Trimmer Capacitor	1-101-007-11	C ₄₀₇	0.05 μ F Ceramic
1-101-072-14	C ₂₀₉	0.01 μ F Ceramic	1-121-121-00	C ₄₀₈	200 μ F 12 V Electrolytic
-125-11	C ₂₁₀	0.001 μ F "	1-101-571-11	C ₄₀₉	140 PF Ceramic
1-141-060-11	C ₂₁₁	Cylindrical Trimmer Capacitor	1-121-104-00	C ₄₁₀	10 μ F 6 V Electrolytic
1-101-556-11	C ₂₁₂	6 PF Ceramic	1-101-007-11	C ₄₁₁	0.05 μ F Ceramic
-559-11	C ₂₁₃	15 PF "	1-121-106-05	C ₄₁₂	5 μ F 6 V Electrolytic
-561-11	C ₂₁₄	30 PF "	-115-05	C ₄₁₃	100 μ F 6 V "
-559-11	C ₂₁₅	15 PF "	1-105-673-12	C ₄₁₄	0.01 μ F Mylar
-573-11	C ₂₁₆	120 PF "	1-121-128-05	C ₄₁₅	50 μ F 10 V Electrolytic
-125-11	C ₂₁₇	0.001 μ F "	-186-05	C ₄₁₆	1000 μ F 12 V "
-565-11	C ₂₁₈	25 PF "	-104-00	C ₅₀₁	10 μ F 6 V "
-553-11	C ₂₁₉	3 PF "	1-101-012-11	C ₅₀₂	5 PF Ceramic
	C ₂₂₀	Fine Tuning Capacitor	1-103-305-11	C ₅₀₃	500 PF Styrol
1-101-554-11	C ₂₂₁	4 PF Ceramic	1-101-113-18	C ₅₀₄	80 PF Ceramic
-572-11	C ₂₂₂	7 PF "	-439-11	C ₅₀₅	700 PF "
-557-11	C ₂₂₃	10 PF "	1-121-110-05	C ₅₀₆	30 μ F 10 V Electrolytic
-563-11	C ₂₂₄	50 PF "	-159-05	C ₅₀₇	100 μ F 10 V "
-125-11	C ₂₂₅	0.001 μ F "	1-105-685-12	C ₅₀₈	0.1 μ F Mylar
-125-11	C ₂₂₆	0.001 μ F "	1-121-148-05	C ₅₀₉	1 μ F 100 V Electrolytic
-544-11	C ₂₂₇	1800 PF "	1-105-681-12	C ₅₁₀	0.047 μ F Mylar
-544-11	C ₂₂₈	1800 PF "	1-127-907-00	C ₆₀₁	3 μ F 6 V Electrolytic (Alox)
-544-11	C ₂₂₉	1800 PF "	-906-00	C ₆₀₂	1 μ F 10 V " (")
-560-11	C ₂₃₀	20 PF "	-906-00	C ₆₀₃	1 μ F 10 V " (")
-555-11	C ₂₃₁	5 PF "	1-105-683-12	C ₆₀₄	0.068 μ F Mylar
-561-11	C ₂₃₂	30 PF "	-679-12	C ₆₀₅	0.033 μ F "
-004-11	C ₃₀₁	0.01 μ F "	-673-12	C ₆₀₆	0.01 μ F "
-004-11	C ₃₀₂	0.01 μ F "	1-127-916-11	C ₆₀₇	0.5 μ F 10 V Electrolytic (Alox)
-072-15	C ₃₀₃	0.01 μ F "	1-105-677-12	C ₆₀₈	0.022 μ F Mylar
-011-11	C ₃₀₄	3 PF "	1-127-919-11	C ₆₀₉	0.2 μ F 25 V Electrolytic (Alox)
1-121-131-00	C ₃₀₅	3 μ F 6 V Electrolytic	-907-00	C ₆₁₀	3 μ F 10 V " (")
1-101-004-11	C ₃₀₆	0.01 μ F Ceramic	1-121-127-05	C ₇₀₁	20 μ F 10 V "
-004-11	C ₃₀₇	0.01 μ F "	-085-11	C ₇₀₂	20 μ F 12 V "
-011-11	C ₃₀₈	3 PF "	-128-05	C ₇₀₃	50 μ F 10 V "
-072-15	C ₃₀₉	0.01 μ F "	1-127-914-00	C ₇₀₄	5 μ F 6 V " (Alox)
-009-11	C ₃₁₀	1 PF "	1-121-127-05	C ₇₀₅	20 μ F 10 V "
-011-11	C ₃₁₁	3 PF "	-127-05	C ₇₀₆	20 μ F 10 V "
1-121-102-00	C ₃₁₂	30 μ F 6 V Electrolytic	-221-11	C ₇₀₇	60 μ F 12 V "
1-101-004-11	C ₃₁₃	0.01 μ F Ceramic	1-127-908-00	C ₇₀₈	3 μ F 10 V " (Alox)
1-121-102-00	C ₃₁₄	30 μ F 6 V Electrolytic	1-105-721-11	C ₇₀₉	0.047 μ F Mylar
1-101-011-11	C ₃₁₅	3 PF Ceramic	-683-12	C ₈₀₁	0.068 μ F "
-093-11	C ₃₁₆	6 PF "	-683-12	C ₈₀₂	0.068 μ F "
-010-11	C ₃₁₇	2 PF "	-677-12	*C ₈₀₃	0.022 μ F "
-095-11	C ₃₁₈	8 PF "	-675-12	*C ₈₀₄	0.015 μ F "
-004-11	C ₃₁₉	0.01 μ F "	1-121-220-11	C ₈₀₅	200 μ F 12 V Electrolytic
-423-11	C ₃₂₀	500 PF "	1-105-665-12	C ₈₀₆	0.022 μ F Mylar
-004-11	C ₃₂₁	0.01 μ F "	1-113-122-11	C ₈₀₇	0.05 μ F 500 V PS
1-127-920-11	C ₃₂₂	0.3 μ F 25 V Electrolytic (Alox)	1-101-592-11	C ₈₀₈	500 PF Ceramic
1-121-145-00	C ₃₂₃	1 μ F 6 V "	-592-11	C ₈₀₉	500 PF "
-116-00	C ₃₂₄	1 μ F 12 V "	-591-11	C ₈₁₀	500 PF "
-102-00	C ₃₂₅	30 μ F 6 V "	-591-11	C ₈₁₁	500 PF "
1-101-004-11	C ₄₀₁	0.01 μ F Ceramic	-591-11	C ₈₁₂	500 PF "
-010-11	C ₄₀₂	2 PF "	1-121-025-11	C ₉₀₁	1900 μ F 15 V Electrolytic
-113-18	C ₄₀₃	80 PF "	-188-05	C ₉₀₂	50 μ F 12 V "
-004-11	C ₄₀₄	0.01 μ F "	-102-05	C ₉₀₃	30 μ F 6 V "
-048-11	C ₄₀₅	4 PF "	-186-05	C ₉₀₄	1000 μ F 12 V "
-115-17	C ₄₀₆	30 PF "	-186-05	C ₉₀₅	1000 μ F 12 V "

Part No.	Description	Q'ty	Part No.	Description	Q'ty
Y-44026-15-1	Tuner Block	1	X-40038-54-1	Power Regulator & Sound Signal Block	1
X-40038-52-1	Video Signal Block <i>P-980-007-</i>	1	1-453-007-11	High Voltage Block	1
X-40043-49-1	Deflection Block <i>P-980-076-</i>	1	1-451-008-12	Deflection Yoke	1

Electrical Parts List (B)

Part No.	Description	Q'ty	Part No.	Description	Q'ty
	Picture Tube		1-203-363-00	Carbon Resistor 560 Ω $\pm 5\%$ 1/8 watt	(2)
73110410}	Picture Tube CT-465	1		Main and Appearance Block	
73110420}			1-501-050-12	Telescopic Antenna, including	1
1-525-062-11	High Voltage Rectifier 1SK2 (Built in High Voltage Block)	(5)	4-003-867-01	Bracket	(1)
	General		-334-01	Antenna Lug	(1)
	Video Signal Block		4-002-717-01	Insulator Bushing	(1)
1-538-175-12	Printed Circuit Board for Video Signal Block	1	-715-01	Antenna Washer	(1)
1-506-108-00	Connecting Pin	1	-728-00	Lock Nut 3 ϕ	(1)
1-507-109-00	Connector Tip	4	-727-00	Nut 3 ϕ	(1)
1-506-065-11	Plug A (Type 7-P)	1	7-623-412-01	Washer 5 ϕ	(1)
	Deflection Block		X-40038-14-3	Telescopic Antenna	(1)
1-538-176-12	Printed Circuit Board for Deflection Block	1	1-545-003-11	Multi-Jack (14 Terms)	1
1-506-108-00	Connecting Pin	8	1-502-101-13	Speaker 40 Ω , 5 cm in Diameter	1
	Power Regulator & Sound Signal Block		-12		
1-538-177-11	Printed Circuit Board for Power Regulator & Sound Signal Block	1	1-507-011-01	Earphone Jack	1
1-506-066-11	Plug B (Type 7-P)	1	-901-02	Earphone Jack Nut	2
	High Voltage Block		1-507-094-11	7 P Jack A	1
1-453-007-11	High Voltage Block, including	1	-095-11	7 P Jack B	1
4-003-890-01	High Voltage Block Case	(1)	1-506-064-11	2 P Plug	1
-891-01	High Voltage Block Tube Mounter	(1)	1-532-044-11	Fuse 1.0 A	1
-892-01	High Voltage Block Shielded Case	(1)	1-526-055-11	Picture Tube Socket	1
-893-01	High Voltage Block Mounting Bracket	(1)	1-535-018-12	Power Receptacle (with 3 Connectors & Fuse Holder)	1
-894-01	Fiber	(1)	1-536-058-11	Connector Tip F	1
1-526-104-11	Anode Connector	(1)	1-507-114-12	2 P Jack	1
1-439-010-11	Horizontal Output Transformer	(1)	-115-11	External Antenna Jack	1
1-525-062-11	High Voltage Rectifier 1SK2	(5)		Tuner Block	
1-101-592-11	Ceramic Capacitor 500 PF \times 2 4 KV	(1)	Y-44026-45-1	Tuner BT-203 W	1
-591-11	" " 500 PF \times 3 4 KV	(1)		Accessories	
1-536-058-11	Connector Tip (F)	(2)	1-534-042-20	Extension Cord	1
4-002-848-01	Screw for Core	(2)	1-504-010-02	Earphone	1
-897-01	Fiber A	(1)	1-534-155-11	AC Power Cord (ACC-2W), including	1
-898-01	Bobbin	(1)	1-441-121-11	Power Transformer	(1)
7-622-105-00	Nut 2 ϕ	(2)	1-530-012-11	Silicon Rectifier	(2)
	Deflection Yoke		4-004-328-01	Trans. Cover A	(1)
1-451-008-12	Deflection Yoke, including	1	-329-01	" " B	(1)
4-003-933-01	Core	(1)	4-003-916-01	AC Plug Right	(1)
-899-01	Yoke Band	(2)	-916-01	" " Left	(1)
-900-01	Terminal Plate	(2)	-918-01	Grommet	(1)
-901-01	Centering Spring	(1)	4-004-330-01	AC Cord with 3 P Plug	(1)
-902-01	Centering Magnet	(2)	-331-01	Cable Clamp	(1)
-903-01	Yoke Cover	(1)	-332-01	Long Screw 53 mm (Long)	(2)
-975-02	Yoke Mounter	(1)	1-201-455-00	Composition Resistor 1.5 M Ω , 1/2 W	(2)
1-536-058-11	Connector Tip (F)	(4)		R _{909, 910}	(2)
7-621-309-55	Screw F 2.6 \times 8	(3)	1-501-047-21	Shoulder Strap Antenna, including	1
1-105-721-11	Eyelet 2 \times 2	(6)	X-40038-24-1	Hook Assembly	(2)
	Mylar Capacitor 0.047 μ F 100 WV	(1)	4-003-930-01	Connection Cord with Plug	(1)
			4-004-327-01	Tag	(1)
			Y-44017-02-3	External Antenna Connector EAC-4	1


Mechanical Parts List

Part No.	Description	Q'ty	Part No.	Description	Q'ty
A. General					
Cabinet & Appearance Items					
X-40038-03-1	Front Panel Assembly, including	1	4-003-857-01	Lid Cushion	(2)
4-003-809-02	Mask	(1)	-858-01	Lid Screw	(1)
-810-01	Panel (left)	(1)	4-004-307-01	Battery Name Plate	(1)
-811-01	Panel Spacer (left)	(1)	-960-01	Specification Label	1
4-004-812-02	Panel (right)	(1)	Main Chassis Block		
4-003-941-02	Panel Spacer (right)	(1)	X-40038-13-2	Chassis Assembly, including	1
-813-01	Picture Tube Escutcheon	(1)	4-003-860-02	Chassis	(1)
X-40038-05-1	SONY Badge Assembly, including	1	-861-01	Post for Battery Pack	(1)
4-003-814-01	Badge Mounter	(1)	-862-01	Post for Signal Circuit Board	(1)
-815-01	Badge "SONY"	(1)	-893-01	Bracket for Multi-Jack	1
4-003-816-01	Front Frame	1	-864-01	Tuner Mounting Plate	1
-817-01	Pull Rod Mounter (A)	2	-865-01	Screw for 2-P Plug	1
-818-01	// " " (B)	2	-961-02	Screw for 2-P Plug (Large)	1
0-209-526-01	Speaker Mounter	2	-984-01	Black Insulating Tape for Signal Circuit Board	1
4-003-819-01	Picture Tube Protector	1	4-002-786-00	Insulating Tape	1
-820-01	Picture Tube Clamp	1	Deflection Block		
-821-01	Pull Rod for Picture Tube	4	4-003-801-01	Heat Sink for Hori. Out. Transistor (2SC41)	1
X-40038-06-4	Cabinet Back Assembly, including	1	-951-01	Heat Sink for Vert. Out. Transistor (2SB381)	1
4-003-822-03	Cabinet Upper Part	(1)	-656-01	Heat Sink for Vert. Out. Transistor (2SD65)	2
-823-02	Cabinet Lower Part	(1)	-803-01	Black Sheet on Deflection Circuit Board	1
-824-02	Joint for Cabinet	(2)	Power Regulator & Sound Signal Block		
-825-02	Badge "SONY"	(1)	4-003-804-01	Heat Sink A	1
X-40038-19-1	Carrying Handle Assembly, including	1	-805-01	// " " B	1
4-003-826-01	Handle	(1)	-806-01	Mylar Tape (Small)	1
-834-01	Leather for Handle	(1)	-807-01	// " " (Large)	1
-827-01	Stand Lock Gear (Stator)	2	-808-01	Insulator for Electrolytic Capacitor	1
-828-01	Stand Lock Gear (Rotor)	2	-656-01	Heat Sink for Transistor (2SD64)	2
-829-01	Wave Washer	2	-953-02	Black Sheet on Power Supply Board	1
-830-01	Handle Shaft	2	Carton and Accessories		
-831-01	Nut for Shaft	2	4-004-319-01	Styro-foam Cushion (A)	1
-832-01	Screw for Shaft	2	X-40038-85-1	Styro-foam Cushion B Assembly, including	1
-833-01	Cover for Washer	2	4-004-320-01	Styro-foam Cushion (B)	(1)
4-002-730-00	Rubber Foot	2	4-003-988-01	Styro-foam Label	(1)
4-003-835-01	Telescopic Antenna Bushing	1	-998-01	Carton Sleeve	1
X-40038-07-2	Fine Tuning Knob Assembly, including	1	-323-02	Sheet for Carton	1
4-003-836-02	Fine Tuning Knob	(1)	-999-01	Master Carton for 4 sets	1/4
-250-01	Spring	(1)	-880-02	Polyethylene Bag	1
X-40038-36-1	Channel Selector Knob Assembly, including	1	-942-01	Hood	1
4-004-837-03	Channel Selector Knob	(1)	4-495-041-10	Instruction Manual	1
-958-01	Face Plate	(1)	X-40038-49-1	Caution Tag Assembly, including	1
4-003-839-01	Spring	(1)	4-003-966-01	Caution Tag	(1)
-840-02	Control Knob	4	4-498-005-01	Instruction (Adjustment)	(1)
-841-02	Volume Control Knob	1	4-003-883-01	Inspection Card	(1)
-842-01	Leather Spacer for Knobs	5	4-004-333-01	Accessory Case	1
X-40038-09-1	Front Cover Assembly, including	1	X-44900-02-1	Polishing Cloth	1
4-003-843-01	Front Cover	(1)	B. Screws & Washers		
-980-01	Front Cover Cushion	(1)	Circuit Board Block		
-844-01	Bracket "A" for Hood	(1)	7-621-559-25	Screw + K2.6 x 4 for Deflection Circuit Board	1
X-40038-10-1	Bracket Assembly for Hood	(1)	-261-29	Screw + P3 x 4 (Polycarbonate) for Power Supply Board	2
X-40038-11-5	Battery Case Assembly, including	1	-35	Screw + P 3 x 5 for Power Supply Board (1)	3
4-003-848-01	Battery Case	(1)	-255-35	Heat Sink (2)	2
-849-01	// " " (Back)	(1)	-261-25	Screw + P 2 x 5 for Heat Sink	2
-850-01	Battery Contactor	(7)	-55	Screw + P 3 x 8 for Heat Sink	2
-851-01	// (Positive & Negative)	(2)	7-623-408-02	Star Washer 3φ for Heat Sink	2
-852-01	// (Negative)	(2)	7-622-108-02	Nut 3φ	2
-853-02	// (Positive)	(1)			
-854-02	Battery Case Clamp Screw L	(1)			
-855-01	// " " " " S	(1)			
-949-01	Spring for Screw	(2)			
-856-01	Battery Spacer	(9)			
	Battery Case Lid	(1)			

—continued—



Part No.	Description	Q'ty	Part No.	Description	Q'ty
7-623-205-12	Spring Washer 2 ϕ for Heat Sink	2		Nut 2 ϕ	6
	Cabinet & Appearance Block		7-624-103-01	Retaining Ring E-4 for Battery Case	2
7-621-720-22	Self Tapping Screw +K 2 \times 5 for SONY		7-624-104-01	Retaining Ring E-2 for Battery Lid	1
	Badge	2	7-623-305-02	Internal Star Washer 2 ϕ	2
7-621-259-72	Self Tapping Screw +P 2.6 \times 6	1	-307-02	" " " 2.6 ϕ for Speaker	1
	for Cabinet Lower Part		-207-11	Spring Washer 2.6 ϕ for Speaker	2
-722-41	Self Tapping Screw +P 3 \times 6 for		-507-01	Solder Lug 2.6 ϕ	1
	Cabinet Lower Part	2		Chassis	
-259-25	Screw +P 2.6 \times 4 for Speaker (2)	10	7-621-259-25	Screw +P 2.6 \times 4 for 3 P Terminal	2
	Cabinet Mask (4)		-261-35	Screw +P 3 \times 5 for High Voltage	7
	Picture Tube (4)			Block (2)	
-262-55	Screw +P 3 \times 25 for Picture Tube Clamp	1		Antenna Mounter (1)	
-559-25	Screw +K 2.6 \times 4 for Chassis	4		Multi-Jack (2)	
-259-29	Screw +P 2.6 \times 4 for Cabinet Upper			Tuner Mounter (2)	
	Part	1	7-623-208-12	Spring Washer 3 ϕ	3
-555-25	Screw +K 2 \times 4	6		Nut 3 ϕ	2
-770-44	Screw +B 2 \times 5	5		Tuner Block	
-559-45	Screw +K 2.6 \times 6 for 2 P Jack	2	7-621-261-35	Screw +P 3 \times 3 for Tuner	3
	Nut 3 ϕ	1			

Exploded Diagram




Exploded Diagram

(2)




(3)





Exploded Diagram

(5)



SONY CORPORATION